



UTTERMOST

ASSEMBLY AND INSTALLATION INSTRUCTIONS

21301

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

Installation Steps

- Carefully unpack your new fixture and lay out all the parts on a clear surface.
- Place the Nipple-2 over the Tube and tighten nipple-2 in Coupling.
- Secure the Tab-1 of the Arms to the Column-1 with the Screws by Wrench, and then secure the Tab-2 of the Arms to the Column-2 with the screws by Wrench.
- Raise the Column-2 onto the Nipple-3, then secure with the Finial and Adjust coupling.
- Hook the crystal drop-1 to the Ring-1, Hook the crystal drop-2 to the Ring-2, Hook the crystal drop-3 to the Finial.
- Thread Hex nut-2 onto Nipple-1, insert Lock washer over the end of Nipple-1, thread Nipple-1 through Mounting bar and secure with Hex nut-1 continue until tight.
- Thread Green ground screw into the hole near the two dimples of Mounting bar. Secure Mounting bar to outlet box with Outlet box screws.
- Weave Fixture Wire and Ground Wire through Chain links. Open Quick link-2, connect Loop to one end link of Chain and close Quick link-2.
- Thread Collar ring to Collar loop, secure Collar loop to Nipple-1 through Canopy. Open Quick link-1, connect Collar loop to the other one link of Chain and close Quick link-1.
- Make Wire connections with Wire Connector:
 - The smooth wire (w/ marking) from fixture to Black Wire from power source.
 - The ribbed wire (w/o marking) from Fixture to White Wire from power source.
 - Attach the Ground Wire and house ground wire to the Mounting bar with the green Ground screw.
 Carefully tuck wires back into the Outlet box.
- After wires are connected, tuck them carefully inside outlet box. Raise Canopy allowing for Nipple-1 to protrude through Canopy and secure with Collar ring.
- Place the Cap onto the Candle sleeve.
- Install the light bulbs in accordance with the fixture's specifications.

DO NOT EXCEED THE MAXIMUM WATTAGE RATING!
- Turn on the power at fuse or Circuit Box.

