Model: EN-OD24100-RB2-T

InvisiLED® Electronic Remote Transformer

WAC LIGHTING

Responsible Lighting®



Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

Low Voltage electronic transformer designed to be used as an enclosed remote transformer. Enclosure has separate compartments for transformer, line and low voltage wiring. Transformer may be safely loaded to 100% of stated capacity.

FEATURES

- Compatible with InvisiLED® Pro Outdoor LED-TO24
- Class 2, UL listed electronic low voltage transformer.
- The enclosure is damp location listed, the waterproof connector is wet location listed
- Built-in auto reset, soft start, short and overload circuit protection features. Soft start delayed start feature extends lamp life.
- Includes 6' lead wire
- In the case of a system overload or short circuit the transformer will
 revert to a "hold" position and then automatically reset the system when
 the problem is solved. System protection is designed to last several hours.

SPECIFICATIONS

Input: 120VAC 0.84A 50/60Hz

Output: 24V AC, 4A, 96W maximum, 1W minimum load **Dimming:** Electronic Low Voltage (ELV) dimmable

Standards: UL & cUL Listed

Ambient Temp: -4°F to 122°F (-20°C to 50°C)

ORDER NUMBER

Model	Output	L	W	Н
EN-OD24100-RB2-T	24V, 96W	6½"	15/8"	13/16"

EN-OD24100-RB2-T