

# INVISILED® ACCESSORIES

Indoor non-color changing electronic accessories

# WAC LIGHTING

Responsible Lighting®

| Type                                                                                                                                                                                                                                                                                                | Model                                                                                                      | Input            | Output                     | Max Run            | Dim        | Compatibility                                                       |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|------------------|----------------------------|--------------------|------------|---------------------------------------------------------------------|
|  <p>Remote<br/><i>Includes a 6 foot lead wire</i></p>                                                                                                                                                              | <b>EN-2460-RB2-T</b><br><b>EN-24100-RB2-T</b>                                                              | 120VAC<br>120VAC | 24VAC / 60W<br>24VAC / 96W | 30 feet<br>40 feet | ELV<br>ELV | Pro, Pro2, Pro3,<br>LITE, Classic                                   |
|  <p>Plug-in<br/><i>Includes a 6 foot lead wire</i></p>                                                                                                                                                             | <b>EN-2460-P-AR-T</b><br><b>EN-24100-P-AR-T</b>                                                            | 120VAC<br>120VAC | 24VAC / 60W<br>24VAC / 96W | 30 feet<br>40 feet | ELV<br>ELV | Pro, Pro2, Pro3,<br>LITE, Classic                                   |
|  <p>Remote 277V<br/><i>Includes a 6 foot lead wire</i></p>                                                                                                                                                         | <b>EN-24100-277-RB2-T</b>                                                                                  | 277VAC           | 24VDC / 96W                | 40 feet            | 0-10V      | Pro, Pro2, Pro3,<br>LITE, Classic                                   |
|  <p>Touch Panel and Motion Sensor<br/><i>Includes a Touch Panel, an Occupancy Sensor, and a Controller<br/>AC/DC input at 12V(60W Max) or 24V(96W Max)<br/>Connect on secondary side of driver/transformer</i></p> | <b>CT-6A-R2</b>                                                                                            |                  |                            |                    |            | Pro, Pro2, Pro3,<br>LITE, Classic<br>Daylight to Sunset,<br>Palette |
|  <p>In Wall Rated Extension Cable<br/><i>Extends distance between a hard wired power supply<br/>or a wiring box to a tape section.</i></p>                                                                        | <b>LED-TC-WEXT-144</b><br><b>LED-TC-WEXT-144-WT</b><br><b>LED-TC-WEXT-240</b><br><b>LED-TC-WEXT-240-WT</b> |                  |                            |                    |            | Black 12 ft<br>White 12 ft<br>Black 20 ft<br>White 20 ft            |
|  <p>In Wall Rated Joiner Cable<br/><i>Connects tape sections. 2 female ends.<br/>1 male to male connector included</i></p>                                                                                       | <b>LED-TC-WIC-144</b><br><b>LED-TC-WIC-144-WT</b><br><b>LED-TC-WIC-240</b><br><b>LED-TC-WIC-240-WT</b>     |                  |                            |                    |            | Black 12 ft<br>White 12 ft<br>Black 20 ft<br>White 20 ft            |
|  <p>Lead Wire<br/><i>Alternative lengths for plug-in power supplies</i></p>                                                                                                                                      | <b>LED-TC-P-2</b><br><b>LED-TC-P-2-WT</b><br><b>LED-TC-P-12</b><br><b>LED-TC-P-12-WT</b>                   |                  |                            |                    |            | Black 2 ft<br>White 2 ft<br>Black 12 ft<br>White 12 ft              |
|  <p>Extension Cable<br/><i>Extends distance between a hard wired power supply<br/>or a wiring box to a tape section</i></p>                                                                                      | <b>LED-TC-EXT-144</b><br><b>LED-TC-EXT-144-WT</b>                                                          |                  |                            |                    |            | Black 12 ft<br>White 12 ft                                          |
|  <p>Low Voltage Wiring Box With Feed<br/><i>Neatly houses connectors for up to<br/>two wires with 12" female feed</i></p>                                                                                        | <b>LED-TC-B-2</b><br><b>LED-TC-B-2-WT</b>                                                                  |                  |                            |                    |            | Black L: 1½ in<br>White W: ¾ in<br>H: 7⁄8 in                        |
|  <p>Low Voltage Wiring Box<br/><i>Neatly houses connections for up to two wires</i></p>                                                                                                                          | <b>LED-T-B</b>                                                                                             |                  |                            |                    |            | L: 1½ in<br>W: ¾ in<br>H: 7⁄8 in                                    |
|  <p>Wiring Box With Switch<br/><i>Use when spanning a large gap in a system layout without leaving<br/>exposed wiring. Optional switch included</i></p>                                                          | <b>TB-S</b>                                                                                                |                  |                            |                    |            | L: 6¼ in<br>W: 1½ in<br>H: 1¼ in                                    |

Compatible with Pro, Pro2, Pro3, LITE, Classic

WAC Lighting  
www.waclighting.com  
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive • Port Washington, NY 11050  
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center  
1750 Archibald Avenue • Ontario, CA 91760  
Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JUL 2017

# INVISILED® ACCESSORIES

Indoor non-color changing electronic accessories

# WAC LIGHTING

Responsible Lighting®

|                                                                                   |                                                   |                       |       |        |
|-----------------------------------------------------------------------------------|---------------------------------------------------|-----------------------|-------|--------|
|  | Joiner Cable<br><br><i>Connects tape sections</i> | <b>LED-TC-IC2</b>     | Black | 2 in   |
|                                                                                   |                                                   | <b>LED-TC-IC2-WT</b>  | White | 2 in   |
|                                                                                   |                                                   | <b>LED-TC-IC6</b>     | Black | 6 in   |
|                                                                                   |                                                   | <b>LED-TC-IC6-WT</b>  | White | 6 in   |
|                                                                                   |                                                   | <b>LED-TC-IC12</b>    | Black | 12 in  |
|                                                                                   |                                                   | <b>LED-TC-IC12-WT</b> | White | 12 in  |
|                                                                                   |                                                   | <b>LED-TC-IC36</b>    | Black | 36 in  |
|                                                                                   |                                                   | <b>LED-TC-IC36-WT</b> | White | 36 in  |
|                                                                                   |                                                   | <b>LED-TC-IC72</b>    | Black | 72 in  |
|                                                                                   |                                                   | <b>LED-TC-IC72-WT</b> | White | 72 in  |
|  | Male to male connector                            | <b>LED-TC-MM</b>      | Black | 50 Qty |

Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette  
Change directionality of tape runs and reuse cut ends of tape.

|                                                                                     |                                                          |                                         |                |
|-------------------------------------------------------------------------------------|----------------------------------------------------------|-----------------------------------------|----------------|
|    | 3-Way "Y" Connector<br><br><i>Connects tape sections</i> | <b>LED-TC-Y</b><br><b>LED-TC-Y-WT</b>   | Black<br>White |
|    | 4-Way "X" Connector<br><br><i>Connects tape sections</i> | <b>LED-TC-X</b><br><b>LED-TC-X-WT</b>   | Black<br>White |
|  | "L" Connector<br><br><i>Connects tape sections</i>       | <b>LED-TC-L</b><br><b>LED-TC-L-WT</b>   | Black<br>White |
|  | End cap<br><br><i>1 cut and 1 male end cap</i>           | <b>LED-TC-EC</b><br><b>LED-TC-EC-WT</b> | Black<br>White |

Compatible with Pro, Pro2, Pro3, LITE, Classic, Palette

|                                                                                     |                                                                                                  |                                               |                 |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|-----------------------------------------------|-----------------|
|  | Signal Wire<br><br><i>Links master and slave controllers. Can be combined for longer lengths</i> | <b>LED-TC24-SW60</b><br><b>LED-TC24-SW120</b> | 60 in<br>120 in |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|-----------------------------------------------|-----------------|

Compatible with Palette

WAC Lighting  
www.waclighting.com  
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive • Port Washington, NY 11050  
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center  
1750 Archibald Avenue • Ontario, CA 91760  
Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JUL 2017